
SSA1535DR







LightSource:
COB

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
36V 150mA

Size:
⌀35*80mm

Power:
7W

Material:
Aluminium


OPTIC:
15°/24°/36°

CRI:
Ra>90

Description:
Track Spotlight

SSA1545DR







LightSource:
COB

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
36V 250mA

Size:
⌀45*100mm

Power:
10W

Material:
Aluminium


OPTIC:
15°/24°/36°

CRI:
Ra>90

Description:
Track Spotlight

SSA1560DR







LightSource:
COB

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
36V 350mA

Size:
⌀60*120mm

Power:
15W

Material:
Aluminium


OPTIC:
15°/24°/36°

CRI:
Ra>90

Description:
Track Spotlight

SLB1514NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
142*35*85mm

Power:
5W

Material:
Aluminium

OPTIC:
100°

CRI:
Ra>90


Description:
Fixed floodlights

COLORS

BK

SLB1528NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
275*35*85mm

Power:
10W

Material:
Aluminium


OPTIC:
100°

CRI:
Ra>90

Description:
Fixed floodlights

SLA1505NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
142*35*85 mm

Power:
5W

Material:
Aluminium


OPTIC:
24°

CRI:
Ra>90

Description:
Fixed grille light

SLA1510NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
270*35*85 mm

Power:
10W

Material:
Aluminium


OPTIC:
24°

CRI:
Ra>90

Description:
Fixed grille light

SSB1514DR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
142*35*117mm

Power:
5W

Material:
Aluminium

OPTIC:
100°

CRI:
Ra>90

Description:
Swivel Floodlight


COLORS

BK

S15 Series

SSB1528DR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
275*35*117mm

Power:
10W

Material:
Aluminium


OPTIC:
100°

CRI:
Ra>90

Description:
Swivel Floodlight

SSA1505DR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
142*35*117 mm

Power:
5W

Material:
Aluminium


OPTIC:
24°

CRI:
Ra>90

Description:
Shaker Grille Lamp

SSA1510DR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
270*35*117 mm

Power:
10W

Material:
Aluminium


OPTIC:
24°

CRI:
Ra>90

Description:
Shaker Grille Lamp

SWA1524NR-A







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
276*118*70mm

Power:
24W

Material:
Aluminium

OPTIC:
60°/90°

CRI:
Ra>90


Description:
Fixed grille light

COLORS

BK

SSA1524DR-A







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
276*118*102mm

Power:
24W

Material:
Aluminium


OPTIC:
60°/90°

CRI:
Ra>90

Description:
Shaker Grille Lamp

SSA1524NR-B







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
506*118*102 mm

Power:
12W*2

Material:
Aluminium


OPTIC:
60°/90°


CRI:
Ra>90

Description:
Fixed grille light without backlight

SSD1524NR-B







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
506*118*102mm

Power:
Downward LED 12W*2
Upper LED 8W

Material:
Aluminium


OPTIC:
60°/90°

CRI:
Ra>90

Description:
Backlit Fixed Grille Lamp

SWA1548NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
1006*118*70 mm

Power:
18W*2

Material:
Aluminium

OPTIC:
60°/90°

CRI:
Ra>90


Description:
Fixed grille light without backlight

COLORS

BK

SWD1548NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
1006*118*70 mm

Power:
Downward LED 18W*2
Upper LED 15W

Material:
Aluminium


OPTIC:
60°/90°

CRI:
Ra>90

Description:
Backlit Fixed Grille Lamp

SWA1536NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
1006*118*70 mm

Power:
12W*3

Material:
Aluminium


OPTIC:
60°/90°

CRI:
Ra>90

Description:
Fixed grille light without backlight

SWB1513NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀113*87mm

Power:
12W

Material:
Aluminium


OPTIC:
100°

CRI:
Ra>90

Description:
Fixed floodlights

SWB1514NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀138*87mm

Power:
20W

Material:
Aluminium

OPTIC:
100°

CRI:
Ra>90


Description:
Fixed floodlights

COLORS

BK

SWB1501NR-A







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀100*156 mm

Power:
5W

Material:
Glass


OPTIC:
100°

CRI:
Ra>90

Description:
Fixed

SWB1501NR-B







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀118*131mm

Power:
5W

Material:
Glass


OPTIC:
100°

CRI:
Ra>90

Description:
Fixed

SWB1501NR-C







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀50*160mm

Power:
3W

Material:
Glass


OPTIC:
100°

CRI:
Ra>90

Description:
Fixed

SWB1502NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀60*120mm

Power:
3W

Material:
Glass

OPTIC:
200°

CRI:
Ra>90

Description:
Fixed


COLORS

WH

S15 Series

SWB1503NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀80*120mm

Power:
3W

Material:
Glass


OPTIC:
200°

CRI:
Ra>90

Description:
Fixed

SWB1504NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀100*160mm

Power:
5W

Material:
Glass


OPTIC:
200°

CRI:
Ra>90

Description:
Fixed

SWB1505NR







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀120*180mm

Power:
5W


Material:
Glass

OPTIC:
200°

CRI:
Ra>90

Description:
Fixed

SPB1502NR





LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀60mm

Power:
3W

Material:
Glass

OPTIC:
200°


CRI:
Ra>90

Description:
Chandelier version

COLORS

BK WH

SPB1504NR





LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀ 100 mm

Power:
5W


Material:
Glass

OPTIC:
200°

CRI:
Ra>90

Description:
Chandelier version

SPB1505NR





LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀120mm

Power:
5W

Material:
Glass


OPTIC:
200°

CRI:
Ra>90

Description:
Chandelier version

SPA4030NR-A







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
36V 120mA

Size:
⌀40*300 mm

Power:
5W

Material:
Aluminium


OPTIC:
15°/24°/36°

CRI:
Ra>90

Description:
Chandelier version

SPA5030NR-A







LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
36V 250mA

Size:
⌀50*300 mm

Power:
10W

Material:
Aluminium

OPTIC:
15°/24°/36°

CRI:
Ra>90


Description:
Chandelier version

COLORS

BK WH

SLS1522-1M





High CRI IP20

LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀22*1000 mm

Power:
16W

Material:
PC


OPTIC:
360°

CRI:
Ra>90

Description:
Flexible Light Bar

SLS1522-2M





High CRI IP20

LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀22*2000mm

Power:
32W

Material:
PC


OPTIC:
360°

CRI:
Ra>90

Description:
Flexible Light Bar

SLS1522-3M





High CRI IP20

LightSource:
LED

CCT:
2700K/3000K/4000K/5000K

Input(V):
48V

Voltage & Current:
48V

Size:
⌀22*3000mm

Power:
48W

Material:
PC

luminous flux:
2835 lm

OPTIC:
360°

CRI:
Ra>90

Description:
Flexible Light Bar

COLORS

WH