
DA4803DR-AA





High CRI · IP20 · 30° · 0-10V · Triac · DALI · Wireless


LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ82x90

Material: aluminum
Power: 12W
Voltage & Current: 36V
Cutout: Φ75

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 890LM

DA4803DRW-AA





High CRI · IP20 · 30° · 0-10V · Triac · DALI · Wireless


LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: 100x90

Material: aluminum
Power: 12W
Voltage & Current: 36V
Cutout: Φ75

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 890LM

DA4803DRZ-AA





High CRI · IP20 · 30° · 0-10V · Triac · DALI · Wireless


LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: 130x90

Material: aluminum
Power: 12W
Voltage & Current: 36V
Cutout: Φ75

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 890LM

DA4803DR-AB





High CRI · IP20 · 30° · 0-10V · Triac · DALI · Wireless

LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ82x90


Material: aluminum
Power: 12W
Voltage & Current: 36V
Cutout: Φ75

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 890LM

black white

DA4803DR-AC





High CRI · IP20 · 30° · 0-10V · Triac · DALI · Wireless


LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ82x90

Material: aluminum
Power: 12W
Voltage & Current: 36V
Cutout: Φ75

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 890LM

DA4803DRW-AC





High CRI · IP20 · 30° · 0-10V · Triac · DALI · Wireless


LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ100x90

Material: aluminum
Power: 12W
Voltage & Current: 36V
Cutout: Φ75

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 890LM

DA4803DRZ-AC





High CRI · IP20 · 30° · 0-10V · Triac · DALI · Wireless


LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ130x90

Material: aluminum
Power: 12W
Voltage & Current: 36V
Cutout: Φ75

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 890LM

DA4803DR-AP





High CRI · IP20 · 30° · 0-10V · Triac · DALI · Wireless

LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ82x90

Material: aluminum
Power: 12W
Voltage & Current: 36V
Cutout: Φ75

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 890LM

black white