

DA4802DRW-AC








LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ90x86


Material: aluminum
Power: 8W
Voltage & Current: 36V
Cutout: Φ55

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 600LM

DA4802DRZ-AC







LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: 108x86

Material: aluminum
Power: 8W
Voltage & Current: 36V
Cutout: Φ55

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 600LM

DA4802DR-AE


LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ65x93


Material: aluminum
Power: 8W
Voltage & Current: 36V
Cutout: Φ55

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 600LM

DA4802DR-AF







LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ65x93


Material: aluminum
Power: 8W
Voltage & Current: 36V
Cutout: Φ55


Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 600LM

black white

DA4802DR-AG








LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ65x93


Material: aluminum
Power: 8W
Voltage & Current: 36V
Cutout: Φ55

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 600LM

DA4802DR-AH







LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ65x114

Material: aluminum
Power: 8W
Voltage & Current: 36V
Cutout: Φ55

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 600LM

DA4802DR-AR


LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ80x118


Material: aluminum
Power: 8W
Voltage & Current: 36V
Cutout: Φ55

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 600LM

DA4802DR-AK







LED brand: OSRAM
CT: 2700K/3000K/4000K
CRI: Ra>90
Size: Φ91x125

Material: aluminum
Power: 8W
Voltage & Current: 36V
Cutout: Φ55

Beam angle: 15°/24°/36°
Mains voltage: 220-240V 50/60Hz
Description: Downlight
Luminousflux: 600LM

black white